


DS-D4480FO-BKI Outdoor Fixed LED Display



- Widely applied in outdoor permanent advertising scenes
- Thin and light cabinet with the die-casting aluminum design
- IP 65 rating for both front and back
- Free of air conditioners with multiple ventilation modes working together inside the cabinets
- Standing, wall mount, and lifting available for installation
- Customizable as stadium LED screens




▪ Specification

	Model	DS-D4480FO-BKI
Cabinet	Pixel Configuration	1R1G1B
	Pixel Pitch Category	P8.0
	Pixel Pitch	8.0 mm
	Modules Component	3 × 6
	Dimensions (W × H × D)	960 mm × 960 mm × 138 mm (37.80" × 37.80" × 5.43")
	Resolution	120 × 120
	Area	0.9216 m ²
	Weight	50 kg (110.23 lb.)
	Pixel Density	15625 dots/m ²
	Lamp Board Housing	With housing
	Cabinet Material	Waterproof sheet metal box
	Maintenance Method	Back maintenance
	Cabinet Flatness	0.2 mm
Protection Level	IP65	
Key Material	Lamp Encapsulation	Nationstar 3535
	Control System	DS-D42C04-N、DS-D42C06-N
Display	White Balance Brightness	5500 nits
	Color Temperature	3500K to 9300K adjustable
	Viewing Angle	Horizontal 140°, vertical 120°
	Contrast Ratio	≥ 5000:1
	Color Uniformity	≤ ± 0.003Cx, Cy
	Brightness Uniformity	≥ 97%
Processing Performance	Driving Method	Constant current driving
	Frame Frequency	60 Hz
	Refresh Rate	Up to 3840 Hz
	Grey Level	Up to 14 bit
	Display Color	16777216
Power	Power Supply	110~220 VAC ± 15%
	Max. Consumption	≤ 1000 W/m ²
	Average Consumption	< 300 W/m ²
Working Environment	Working Temperature	-20 °C to 50 °C (-4 °F to 120 °F)
	Working Humidity	10%~80%RH
	Storage Humidity	10%~85%RH
	Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
General	Gross Weight	270 kg /5 in 1 (595.25 lb.)
	Package Dimension (W × H × D)	1370 mm × 1090 mm × 1180 mm (53.93" × 43.91" × 46.46")
	Lifespan	Lamp 100,000 hours


▪ Available Model

DS-D4480FO-BKI

▪ Dimension



Distributed by

**HIKVISION®****Headquarters**

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
overseasbusiness@hikvision.com

Hikvision USA
T +1-909-895-0400
sales.usa@hikvision.com

Hikvision Australia
T +61-2-8599-4233
salesau@hikvision.com

Hikvision India
T +91-22-28469900
sales@pramahikvision.com

Hikvision Canada
T +1-866-200-6690
sales.canada@hikvision.com

Hikvision Thailand
T +662-275-9949
sales.thailand@hikvision.com

Hikvision Europe
T +31-23-5542770
sales.eu@hikvision.com

Hikvision Italy
T +39-0438-6902
info.it@hikvision.com

Hikvision Brazil
T +55 11 3318-0050
Latam.support@hikvision.com

Hikvision Turkey
T +90 (216)521 7070- 7074
sales.tr@hikvision.com

Hikvision Malaysia
T +601-7652-2413
sales.my@hikvision.com

Hikvision UK & Ireland
T +01628-902140
sales.uk@hikvision.com

Hikvision South Africa
Tel: +27 (10) 0351172
sale.africa@hikvision.com

Hikvision France
T +33(0)1-85-330-450
info.fr@hikvision.com

Hikvision Kazakhstan
T +7-727-9730667
nikia.panfilov@hikvision.ru

Hikvision Vietnam
T +84-974270888
sales.vt@hikvision.com

Hikvision UAE
T +971-4-4432090
salesme@hikvision.com

Hikvision Singapore
T +65-6684-4718
sg@hikvision.com

Hikvision Spain
T +34-91-737-16-55
info.es@hikvision.com

Hikvision Tashkent
T +99-87-1238-9438
uzb@hikvision.ru

Hikvision Hong Kong
T +852-2151-1761
info.hk@hikvision.com

Hikvision Russia
T +7-495-669-67-99
saleru@hikvision.com

Hikvision Korea
T +82-(0)31-731-8817
sales.korea@hikvision.com

Hikvision Poland
T +48-22-460-01-50
info.pl@hikvision.com

Hikvision Indonesia
T +62-21-2933759
Sales.Indonesia@hikvision.com

Hikvision Colombia
sales.colombia@hikvision.com